

Garmin GPSMAP 723, 923 and 1223 Specifications

| | GPSMAP 723 | GPSMAP 923 | GPSMAP 1223 |
|-------------------------------------|--|--|--|
| General | | | |
| PHYSICAL DIMENSIONS | 7.6" x 5.5" x 2.9" (19.2 x 14.0 x 7.4 cm) | 9.2" x 6.4" x 3" (23.3 x 16.2 x 7.6 cm) | 12.1" x 8.9" x 3.2" (30.8 x 22.8 x 8.2 cm) |
| DISPLAY SIZE | 6.1" x 3.5"; 7.0" diagonal | 7.8" x 4.4"; 9.0" diagonal | 10.3" x 6.4"; 12.1" diagonal |
| | (15.4 x 9.1 cm; 17.8 cm diagonal) | (19.9 x 11.2 cm; 22.9 cm diagonal) | (26.2 x 16.3 cm; 30.7 cm diagonal) |
| DISPLAY RESOLUTION | 1024 x 600 pixels | 1280 x 720 pixels | 1280 x 800 pixels |
| DISPLAY TYPE | WSVGA display | WXGA display | WXGA display |
| WEIGHT | 2.8 lbs (1.3 kg) | 3.6 lbs (1.6 kg) | 6.6 lbs. (3.0 kg) |
| WATER RATING | IPX7 | IPX7 | IPX7 |
| POLARIZED SUPPORT | ✓ | ✓ | ✓ |
| POWER CONSUMPTION | Max power usage at 10 Vdc: 17.6 W | Max power usage at 10 Vdc: 22 W | Max power usage at 10 Vdc: 26.5 W |
| | Typical current draw at 12 Vdc: 1.1 A | Typical current draw at 12 Vdc: 1.3 A | Typical current draw at 12 Vdc: 1.7 A |
| | Max current draw at 12 Vdc: 1.5 A | Max current draw at 12 Vdc: 1.8 A | Max current draw at 12 Vdc: 2.2 A |
| ANTENNA | Internal or external over NMEA 2000 | Internal or external over NMEA 2000 | Internal or external over NMEA 2000 |
| MOUNTING OPTIONS | Bail, flush or flat | Bail, flush or flat | Bail or flush |
| RECEIVER | 10 Hz high-sensitivity | 10 Hz high-sensitivity | 10 Hz high-sensitivity |
| GARMIN MARINE NETWORK™ PORTS | 1 | 1 | 2 |
| Maps & Memory | | | |
| PRELOADED MAPS | worldwide basemap | worldwide basemap | worldwide basemap |
| ACCEPTS DATA CARDS | 2 microSD™ cards (back of unit) | 2 microSD™ cards (back of unit) | 2 microSD™ cards (back of unit) |
| WAYPOINTS | 5,000 | 5,000 | 5,000 |
| TRACK LOG | 50,000 points; 50 saved tracks | 50,000 points; 50 saved tracks | 50,000 points; 50 saved tracks |
| ROUTES | 100 | 100 | 100 |
| Outdoor Recreation | | | |
| TIDE TABLES | ✓ | ✓ | ✓ |
| Chartplotter Features | | | |
| GARMIN RADAR COMPATIBLE | ✓ | ✓ | ✓ |
| GARMIN SONAR COMPATIBLE | Yes (with external black box, sold separately) | Yes (with external black box, sold separately) | Yes (with external black box, sold separately) |

| | | | |
|--|---|---|---|
| GARMIN SMARTMODE COMPATIBLE (CUSTOMIZABLE MONITOR PRESETS) | ✓ | ✓ | ✓ |
| SUPPORTS AIS (TRACKS TARGET SHIPS POSITION) | ✓ | ✓ | ✓ |
| SUPPORTS DSC (DISPLAYS POSITION DATA FROM DSC-CAPABLE VHF RADIO) | ✓ | ✓ | ✓ |
| SUPPORTS FUSION-LINK™ COMPATIBLE RADIOS | ✓ | ✓ | ✓ |
| GSD™ BLACK BOX SONAR SUPPORT | ✓ | ✓ | ✓ |
| GCV™ BLACK BOX SONAR SUPPORT | ✓ | ✓ | ✓ |
| ACTIVECAPTAIN COMPATIBLE | ✓ | ✓ | ✓ |
| GRID™ (GARMIN REMOTE INPUT DEVICE) COMPATIBLE | ✓ | ✓ | ✓ |
| WIRELESS REMOTE COMPATIBLE | ✓ | ✓ | ✓ |
| SAILING FEATURES | ✓ | ✓ | ✓ |

Sonar Features & Specifications

| | | | |
|---|--|--|--|
| DUAL-FREQUENCY (50/200 KHZ) SONAR CAPABLE | x | x | Yes (with external black box, sold separately) |
| DUAL-BEAM (77/200 KHZ) SONAR CAPABLE | x | x | Yes (with external black box, sold separately) |
| CHIRP SONAR TECHNOLOGY | Yes (with external black box, sold separately) | Yes (with external black box, sold separately) | Yes (with external black box, sold separately) |
| CLEARVÜ | Yes (with external black box, sold separately) | Yes (with external black box, sold separately) | Yes (with external black box, sold separately) |
| SIDEVÜ | Yes (with external black box, sold separately) | Yes (with external black box, sold separately) | Yes (with external black box, sold separately) |

Connections

| | | | |
|------------------------|------------------|------------------|--------|
| NMEA 2000® COMPATIBLE | ✓ | ✓ | ✓ |
| NMEA 0183 INPUT PORTS | 1 (Differential) | 1 (Differential) | 1 |
| NMEA 0183 OUTPUT PORTS | 1 (Differential) | 1 (Differential) | 1 |
| VIDEO INPUT PORTS | 1 BNC | 1 BNC | 1 BNC |
| VIDEO OUTPUT PORTS | x | x | 1 HDMI |
| WIRELESS CONNECTIVITY | ✓ | ✓ | ✓ |
| J1939 COMPATIBLE | ✓ | ✓ | ✓ |
| J1939 Connector | x | x | ✓ |