

## Garmin Reactor 40 Hydraulic Corepack with SmartPump v2 Specifications (010-00705-79)

Dimensions (H x W x D): 7 3/4" x 7 1/2" x 9 5/8" (197 mm x 190 mm x 244 mm)

Weight: 16.5 lbs (7.5 kg)

Temperature range: From 5°F to 131°F (from -15°C to 55°C)

Material: Electronics Control Unit (ECU) - fully gasketed, aluminum alloy; bracket - carbon steel; manifold - aluminum alloy; motor - aluminum alloy

Power cable length: 9 ft (2.7 m)

Power input: 11.5-30 Vdc

Fuse: 40 A, blade-type

Main power usage: standby - less than 1 A; engaged - 5-10 A; peak - 34 A

Flow rate: Configurable from 0 to 2.4 L per minute

Compatible with steering cylinder sizes from 4-24 cu in; 7 second lock to lock up to 17 cu in

### CCU Specifications

Dimensions: 3 19/32" diameter (91.4 mm)

Weight: 5.6 oz (159 g)

Temperature range: From 5°F to 131°F (from -15°C to 55°C)

Case material: Fully gasketed, high-impact plastic, waterproof to IEC 529 IPX7 standards

CCU cable length: 9.5 ft (3 m)

NMEA 2000 power input: 9-16 V

NMEA 2000 LEN: 3 (150 mA)

### GHC 20 Specifications

Unit dimensions, WxHxD: 4.3 " x 4.4 " x 1.9 " (10.9 x 11.2 x 4.8 cm)

Display resolution, WxH: 320 x 240 pixels

Display type: QVGA color LCD display

NMEA output: NMEA 0183, NMEA 2000®

Supply voltage: Powered by NMEA 2000 bus, 9-16 VDC, units operate up to 32 VDC

Operating temperature: -15° C to 70 C° (5° F to 158° F)

Max power consumption: 3W

Viewing angle: 170°

Brightness: 1200 cd/m<sup>2</sup> (NIT)

Water rating: IPX7

NMEA 2000 LEN (Load Equivalency Number): 7 (350 mA at 9VDC)

### Buzzer/Alarm Specifications

Dimensions (L x Diameter): 29/32" x 1.0" (23 mm x 25 mm)

Weight: 2.4 oz (68 g)

Temperature range: from 5°F to 131°F (from -15°C to 55°C)

Cable length: 10 ft (3.0 m)