

# Garmin STRIKER Vivid 7sv Specifications

| General   |   |
|---|---|
| PHYSICAL DIMENSIONS   | 9.3" x 5.5" x 2.3" (23.5 x 14.0 x 5.8 cm) |
| DISPLAY RESOLUTION  | 800 x 480 pixels                          |
| DISPLAY TYPE  | WVGA color                                |
| WEIGHT  | 1.7 lbs (0.8 kg)                          |
| <a href="#">WATER RATING</a>  | IPX7                                      |
| TRANSMIT POWER  | 500 W (RMS)                               |
| Sonar Features & Specifications                                     |   |
| DUAL-FREQUENCY (50/200 KHZ) SONAR CAPABLE                           | ✓   |
| DUAL-BEAM (77/200 KHZ) SONAR CAPABLE                                | ✓   |
| FREQUENCIES SUPPORTED   | Traditional: 50/77/200 kHz                |
|   | CHIRP (mid and high)                      |
|   | ClearVü and SideVü 260/455/800 kHz        |
| BOTTOM LOCK (SHOWS RETURN FROM THE BOTTOM UP)                       | ✓   |
| WATER TEMPERATURE LOG AND GRAPH                                     | ✓   |
| Fishfinder Features   |   |
| SPLIT-SCREEN ZOOM   | ✓   |
| ULTRASCROLL® (DISPLAYS FISH TARGETS AT HIGHER BOAT SPEEDS)          | ✓   |
| FISH SYMBOL ID (HELPS IDENTIFY FISH TARGETS)                        | ✓   |
| AUTOGAIN TECHNOLOGY (MINIMIZES CLUTTER, MAXIMIZES TARGETS)          | ✓   |
| ADJUSTABLE DEPTH LINE (MEASURES DEPTH OF UNDERWATER OBJECTS)        | ✓   |
| A-SCOPE (REAL TIME DISPLAY OF FISH PASSING THROUGH TRANSDUCER BEAM) | ✓   |
| WATER TEMPERATURE SENSOR INCLUDED                                   | ✓   |
| Additional  |   |
| ADDITIONAL  | One 4-pin transducer port                 |
|   | One 4-pin SideVü transducer port          |
|   | Wireless Connectivity: Yes                |
|   | Quickdraw Contours                        |
|   | Integrated GPS                            |
|   | Mark Waypoints                            |
|   | Course over Ground (COG)                  |
| Current draw @ 12V: 0.67A   |   |