

Lowrance HOOK Reveal 9 Specifications

Screen Brightness	>1000 NITS
Weight	1.90 lb (0.86 kg)
Power Consumption max	1.50A @ 13VDC with backlight on full
Power Consumption typical	1.50A @ 13VDC with backlight on full
Power Consumption min	1.50A @ 13VDC with backlight on full
GPS	1 Hz GPS/GLONASS/WAAS/EGNOS/MSAS
Warranty Period	1 Year
Shock Vibration	100,000 cycles of 20 G
Compass Safe	12" (300mm)
Supply Voltage	12v DC (10.8-17VDC)
Waypoints, Routes, Tracks	3000 Waypoints, 100 Routes, 100 Trails
Time to First Fix	30s
Storage Temperature Range	4°F to 140°F (-20°C to 60°C)
Operating Temperature Range	5°F to 131°F (-15°C to 55°C)
Recommended Fuse Rating	5A
Humidity	60°C, 95% relative humidity (RH) for 18 hours
Dimensions W x H x D	10.92" (277.3 mm) x 6.90 (175.2 mm) x 4.42" (112.3 mm)
Viewing Angles	80° top/bottom, 85° left/right
Display Resolution	800 x 480
Charts supported	C-MAP Lake Insight HD, C-MAP Insight Pro, C-MAP (MAX N, MAX N+), C-MAP Genesis, Genesis Live C-MAP, Precision Contour HD (AMER ONLY), Navionics (Gold, NAV+ Platinum+), Insight (Pro and HD), Lowrance Regional Mapping Partners(No Photo/Satellite Overlay)
Cartography included	Navionics+ US/Canada
Correction	DGPS, WAAS
Approvals Compliance	FCC, Industry Canada, Radio Equipment Directive, ACMA, RSM
Mounting Type	Gimbal Bracket, Front Dash Flush Mount
Sonar Compatibility	Integrated:CHIRPBroadbandDownScan
Waterproofing	IPX7 with card door closed
Interface	Keypad: 8-way directional keypad
SD Card Storage	Micro SD Card(32 gb Max)
Backlight Color	Pure White LED