

<b>SmartOne C Specifications &amp; Features:</b>	
<b>Network:</b>	GlobalStar
<b>Power Source:</b>	4 x Lithium AAA Batteries (not included)
<b>Battery Life:</b>	1.5+ years
<b>Antenna:</b>	Internal GPS
<b>Weight:</b>	3.6oz/102g (with 4 batteries and mounting hardware)
<b>Operating Temperature:</b>	-30 to +60°C NOTE: The unit shall remain operational over the -40° to +85°C range, though may experience battery life and RF signal degradation
<b>Device Events:</b>	<ul style="list-style-type: none"> <li>• Wake, sleep</li> <li>• Low battery warnings</li> <li>• Reporting schedule triggered by alarm, motion &amp; distance moved</li> <li>• Engine runtime reporting and major fault monitoring</li> <li>• Ignition on/off</li> <li>• I/O sensors, diagnostics</li> </ul>
<b>Location Monitoring:</b>	<ul style="list-style-type: none"> <li>• GPS position, 12 programmable position reporting settings</li> <li>• Motion sensing, vibration parameters</li> </ul>
<b>Target Assets:</b>	Intelligent management of powered and non-powered fixed and movable assets
<b>Certifications:</b>	<ul style="list-style-type: none"> <li>• FCC CFR Parts 15 and 25</li> <li>• Industry Canada</li> <li>• CE Mark (European Certification)</li> <li>• COFETEL</li> </ul>
<b>Standards:</b>	<ul style="list-style-type: none"> <li>• SAE J1455 MIL STD 810</li> <li>• NEMA 4X / IP68</li> <li>• RoHS Compliant</li> </ul>